


Led light modules



11.81" x 11.81" x 3.54"
300 x 300 x 90 mm



Frame	Box: Aluminum Frame: Anodized aluminum
Power	110 VAC, 60 Hz
Front panel	Special led opal
Dimmable	Dimming control
Operating temperature	0 °C - + 60 °C
Life time	50.000 h with a 30 % decrease in luminous flux
Warranty	Light unit: 6 years

Made in Finland

www.candeeffect.com

Candee F.

We reserve the right to make changes to our products

Led light modules



Recessed light module 11.81" x 11.81" x 3.54" (300 x 300 x 90 mm)

Product code	Model	Frame	Colour	W	K	Led
CEL120 140 270	SQ Light module 300	Aluminum	neutral white	20	4000	Rebel
CEL120 140 370	SQ Light module 300	Aluminum	cool white	20	6000	Rebel

Available in different shapes and sizes.



We reserve the right to make changes to our products

Candee F.

Made in Finland

www.candeeffect.com

Led light modules, special solutions



38.98" x 3.94" x 2.76"
990 x 100 x 70 mm

Frame	Aluminum
Power	110 VAC, 60 Hz
Front panel	Special led opal
Dimmable	Dimming control
Operating temperature	0 °C - + 60 °C
Life time	50.000 h with a 30 % decrease in luminous flux
Warranty	Light unit: 6 years

Linear light module

Led light modules, special solutions



Recessed linear light module 38.98" x 3.94" x 2.76" (990 x 100 x 70 mm)

Product code	Model	Frame	Colour	W	K	Led
CEL120 143 270	Linear light module 990	Aluminum	neutral white	stair: 21 W	4000	Rebel
CEL120 143 370	Linear light module 990	Aluminum	cool white	stair: 21 W	6000	Rebel

Available in different shapes and sizes.

